

GEGRÜNDET 1892

Rektol Klassik. Korbach



Fabrik und Grosshandlung
individueller Öle und Fette

REKTOL 2T/50

Rektol 2T/50 is a high viscosity 2 stroke engine oil for separate and mixed lubrication, especially developed for motorcycles of the post war time equipped with 2 stroke engines from the 1950s.

- Pure mineral oil with reduced sulphate ash and sulphur content
- Reduced flash point for better combustion
- Smokeless combustion
- Contains cleaning additives according to API TA, Jaso FA
- Very good compatibility with usual sealing materials and paints
- Reliable lubrication film at high operating temperatures

This oil is a high viscosity mineral lubricant for use in 2 stroke engines of the post war time, which also suitable for transmissions with oil bath clutch, where the SAE 50 viscosity is required.

SPECIFICATIONS

API-TA; JASO FA
API GL 1+

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,885
Flash point	°C	DIN ISO 2592	< 185
Pour point	°C	DIN ISO 3016	- 18
Viscosity at 40°C	mm ² /sec	DIN 51562	185
Viscosity at 100°C	mm ² /sec	DIN 51562	17,8
TBN	mg KOH/g	ASTM D-2896	0,85
Sulphate ash	%wt.	ASTM D-874	< 0,04
Sulphur	%wt.	DIN ISO 14596	< 0,2

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de