

REKTOL ATF 100-F

Rektol ATF 100-F is a special Ford transmission fluid for automatic transmissions without friction modifiers. At the time for example for Ford C4 automatic transmission.

- outstanding low temperature behavior
- high load carrying capacity
- extended service life, resistant to oxidation
- improved wear protection
- not foaming
- stable lubricating film at high oil temperatures

The original oil formulation according to specification was an inherent part of our product range in our in-house production until the 1970s.

SPECIFICATIONS

| ATF TYPE F | HISTORIC TERMS: |
|------------|------------------------------------|
| FORD | FORD M2C33-D/F/G, Ford M2C-9007 AA |
| | |

TYPICAL CHARACTERISTICS

| Density at 15°C | g/ml | DIN 51757 | 0,865 |
|--------------------|---------|--------------|-------|
| Flash point | °C | DIN ISO 2592 | >185 |
| Pour point | °C | DIN ISO 3016 | - 42 |
| Viscosity at 40°C | mm²/sec | DIN 51562 | 43,0 |
| Viscosity at 100°C | mm²/sec | DIN 51562 | 7,3 |
| _ | | | |

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018

