

GEGRÜNDET 1892

Rektol Klassik, Korbach



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL ATF 300

Rektol ATF 300 is a transmission fluid for automatic transmissions and power steering systems according to specifications of General Motors, Allison, Ford, Mercedes Benz, VOLVO ...

- outstanding low temperature behavior
- high load carrying capacity
- extended service life, resistant to oxidation
- improved wear protection
- not foaming
- stable lubricating film at high oil temperatures

The original oil formulation according to specification was an inherent part of our product range in our in-house production since the 1990s.

SPECIFICATIONS

DEXRON III

HISTORIC TERMS:

GM DEXRON III G,H, ALLISON C-4, FORD MERCON, MERCEDES
BENZ 236.1, 236.5, VOLVO 97341, ATF-III

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,865
Flash point	°C	DIN ISO 2592	>185
Pour point	°C	DIN ISO 3016	- 42
Viscosity at 40°C	mm ² /sec	DIN 51562	43,0
Viscosity at 100°C	mm ² /sec	DIN 51562	8,1

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de