

GEGRÜNDET 1892

# Rektol Klassik. Korbach



Fabrik und Grosshandlung  
individueller Öle und Fette

## REKTOL GEAR 100 SAE 140

Mineral gear oils, without hypoid (EP) additives. Especially suitable for gears and axles equipped with sensitive non-ferrous metal components and "old" sealing materials. It corresponds to the Performance API GL-2. The non-ferrous and seal compatibility is comparable to API GL-1.

- highly adhesive and pressure resistant lubrication film
- outstanding oxidation stability
- excellent air release property, not foaming
- neutral towards sealing materials

The original formulation according to specification were an integral part of our sales range until the 1960s.

### SPEZIFIKATIONEN

SAE 140  
API GL 1 (NO CORROSION FOR NON-FERROUS METALS)  
API GL 2 (WEAR PROTECTION)  
HISTORIC TERMS: OPEL M23

### TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,90
Flash point	°C	DIN ISO 2592	>240
Pour point	°C	DIN ISO 3016	- 10
Viscosity at 40°C	mm <sup>2</sup> /sec	DIN 51562	400
Viscosity at 100°C	mm <sup>2</sup> /sec	DIN 51562	29

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: [info@rektol.de](mailto:info@rektol.de) · Internet: [www.rektol.de](http://www.rektol.de)