

GEGRÜNDET 1892

Rektol Klassik, Korbach



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL GEAR 100 SAE 80

Mineral gear oils, without hypoid (EP) additives. Especially suitable for gears and axles equipped with sensitive non-ferrous metal components and "old" sealing materials. It corresponds to the Performance API GL-2. The non-ferrous and seal compatibility is comparable to API GL-1.

- highly adhesive and pressure resistant lubrication film
- outstanding oxidation stability
- excellent air release property, not foaming
- neutral towards sealing materials

The original formulation according to specification were an integral part of our sales range until the 1960s.

SPEZIFIKATIONEN

SAE 80
API GL 1 (NO CORROSION FOR NON-FERROUS METALS)
API GL 2 (WEAR PROTECTION)
HISTRORIC TERMS: OPEL M15/1

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,87
Flash point	°C	DIN ISO 2592	>205
Pour point	°C	DIN ISO 3016	- 20
Viscosity at 40°C	mm ² /sec	DIN 51562	72
Viscosity at 100°C	mm ² /sec	DIN 51562	11

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de