

GEGRÜNDET 1892

Rektol Klassik. Korbach



Fabrik und Grosshandlung
individueller Öle und Fette

REKTOL GEAR 300 SAE 140

Mild EP- transmission oils for manual- and special transmissions as well as axle drives (Hypoid) under medium operating conditions. It meets the API GL3 and GL4 specifications. Low oxidation effect against non-ferrous metals. No impact on historical sealing materials.

- highly adhesive and pressure resistant lubrication film
- outstanding oxidation stability
- good wear protection due to EP additives (extreme pressure)
- excellent air release property, not foaming
- neutral towards sealing materials

The original oil formulation according to specification was an inherent part of our product range in our in-house production until the 1980s.

SPEZIFIKATIONEN

SAE 140	HISTORIC TERMS:
API GL 3/4	MIL-L-2105, MIL-L-2105-A, MPL, HY, HYP, EP, OPEL M12 (PERFORMANCE)

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,90
Flash point	°C	DIN ISO 2592	>240
Pour point	°C	DIN ISO 3016	- 14
Viscosity at 40°C	mm ² /sec	DIN 51562	400
Viscosity at 100°C	mm ² /sec	DIN 51562	29

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de