

GEGRÜNDET 1892

# Rektol Klassik. Korbach



Fabrik und Grosshandlung  
individueller Öle und Fette

## REKTOL GEAR 500 LS SAE 80W-90

Rektol Gear 500 LS SAE 80W-90 is a special Hypoid gear oil with limited slip additives, designed for extreme requirements in limited slip differentials, especially in plate type differentials.

- highly adhesive and pressure resistant lubrication film
- outstanding oxidation stability
- good wear protection due to EP additives (extreme pressure)
- excellent air release property, not foaming
- neutral towards sealing materials

The original oil formulation according to specification was an inherent part of our product range in our in-house production from the 1970s.

### SPEZIFIKATIONEN

SAE 80W-90	HISTORIC TERMS:
API GL 5	M2C-104A, LIMITED SLIP

### TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,89
Flash point	°C	DIN ISO 2592	>230
Pour point	°C	DIN ISO 3016	- 18
Viscosity at 40°C	mm <sup>2</sup> /sec	DIN 51562	165
Viscosity at 100°C	mm <sup>2</sup> /sec	DIN 51562	16

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: [info@rektol.de](mailto:info@rektol.de) · Internet: [www.rektol.de](http://www.rektol.de)