

GEGRÜNDET 1892

# Rektol Klassik. Korbach



Fabrik und Grosshandlung  
individueller Öle und Fette

## REKTOL HYD 68

Rektol HYD 68 is an ageing resistant hydraulic oil according to DIN 51524 part 1 (HL) with very good cold and warm behaviour and also with an excellent separation ability from air and water. The chemical stability of this oil is very high. It prevents corrosion and does not attack common seals.

- outstanding viscosity-temperature behavior
- ageing resistant
- very durable at high pressure level
- good air release property, not foaming
- effective corrosion protection
- reliable wear protection
- neutral towards sealing materials

The original oil formulation according to specification was an inherent part of our product range in our in-house production from the 1970s until the 1980s.

### SPECIFICATIONS

DIN 51524 HL (< 1985)  
ISO VG 68

### TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,87
Flash point	°C	DIN ISO 2592	>215
Pour point	°C	DIN ISO 3016	- 23
Viscosity at 40°C	mm <sup>2</sup> /sec	DIN 51562	68,0
Viscosity at 100°C	mm <sup>2</sup> /sec	DIN 51562	8,8

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: [info@rektol.de](mailto:info@rektol.de) · Internet: [www.rektol.de](http://www.rektol.de)