

GEGRÜNDET 1892

Rektol Klassik. Korbach



Fabrik und Grosshandlung
individueller Öle und Fette

REKTOL PRESELECTION TRANSMISSION OIL

Gear Oil for WILSON - preselection transmission and the license products from Talbot, Armstrong Siddeley, Daimler and E.N.V..

- pressure resistant lubrication film
- outstanding oxidation stability
- excellent air release property, not foaming
- neutral towards sealing materials

The original formulation according to specification were an integral part of our sales range until the 1950s.

SPEZIFIKATIONEN

SAE 30
API SA
API GL-1

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,87
Flash point	°C	DIN ISO 2592	>215
Pour point	°C	DIN ISO 3016	- 17
Viscosity at 40°C	mm ² /sec	DIN 51562	100
Viscosity at 100°C	mm ² /sec	DIN 51562	11

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de