

GEGRÜNDET 1892

Rektol Klassik. Korbach



Fabrik und Grosshandlung
individueller Öle und Fette

REKTOL SHOCK OIL 30 (HARD)

Rektol Shock Oil 10 is a special hydraulic shock absorber oil for the most single and double acting shock absorbers. Also suitable for lever arm shock absorbers. It contains LS additives (limited slip additives), which counteracts to the undesirable "Stick-Slip" effect.

- outstanding viscosity-temperature behavior
- ageing resistant
- very durable at high pressure level
- good air release property, not foaming
- effective corrosion protection
- reliable wear protection
- neutral towards sealing materials

The original oil formulation according to specification was an inherent part of our product range in our in-house production from the 1980s.

SPECIFICATIONS

DIN 51524 HVLP + LS
SAE 30 (HARD)

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,88
Flash point	°C	DIN ISO 2592	>220
Pour point	°C	DIN ISO 3016	- 19
Viscosity at 40°C	mm ² /sec	DIN 51562	100
Viscosity at 100°C	mm ² /sec	DIN 51562	11

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de