

GEGRÜNDET 1892



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL SPRAY OIL GRAPHIT 22

Graphitized underbody preservative oil for every kind of vehicles.
It provides the same corrosion protection as Rektol Spray Oil Clear and contains additionally graphite EP additives for permanent lubrication of moving parts.

- easy spraying properties with usual spraying equipment
- suitable for apply with a brush
- outstanding oxidation stability, long service life
- counteracts to the oxidation tendency of metals
- good creeping properties
- high solid lubricant content (graphite)

Furthermore this spray oil is also suitable as universal oil for sewing machines, fine mechanics etc.

SPECIFICATIONS

API-SA
GRAPHITIZED - BLACK COLOUR

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,86
Flash point	°C	DIN ISO 2592	>200
Pour point	°C	DIN ISO 3016	- 10
Viscosity at 40°C	mm ² /sec	DIN 51562	22,0
Viscosity at 100°C	mm ² /sec	DIN 51562	4,1

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de