

GEGRÜNDET 1892

Rektol Klassik. Korbach



Fabrik und Grosshandlung
individueller Öle und Fette

REKTOL TOU 15W-30

Tractor Oil Universal (Transmission-, Hydraulic Oil) for wet brakes and wet clutches according to the specifications of Massey Ferguson, Ford, John Deere, IHC, Hanomag and Fiat..

- highly adhesive and pressure resistant lubrication film
- outstanding oxidation stability
- excellent air release property, not foaming
- neutral towards sealing materials

The original formulation according to specification were an integral part of our sales range until the 1990s.

SPEZIFIKATIONEN

SAE 15W-30

SAE 80, API GL 3/4, HVLP 68

HISTORIC TERMS:

MASSEY FERGUSON M 1129, M 1135; FORD M2C - 85 A, - 86A, - 134A; JOHN DEERE J 14 B, J 20 A; IHC B 6 (HYTRAN FLUID); HANOMAG 508 UND FIAT AF 87

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,87
Flash point	°C	DIN ISO 2592	>215
Pour point	°C	DIN ISO 3016	- 20
Viscosity at 40°C	mm ² /sec	DIN 51562	75
Viscosity at 100°C	mm ² /sec	DIN 51562	11,5

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de