

GEGRÜNDET 1892

# Rektol Klassik, Korbach



Fabrik und Grosshandlung  
individueller Oele und Fette

## REKTOL REGULAR 10

Non-Detergent, monograde engine oils manufactured from high quality mineral base oils with oxidation inhibitors (reduces oil ageing) and pour point improver (improves flow rating in the cold). Especially suitable for old engines from the pre-war period, where sludge must settle in the oil sump, because no oil filter exists. This oil has no effect on old seals (leather, paper, cork, rubber ...) and non-ferrous metals, especially white metals (tin-lead alloy).

- good cold start behaviour
- rapidly build up oil pressure
- stable lubricating film
- without any cleaning effect

The original oil formulation according to specification API SA (Regular) was an inherent part of our product range in our in-house production until the 1950s

### SPECIFICATIONS

SAE 10	HISTORICAL TERMS
API SA (REGULAR)	API ML-SERVICE, OPEL M24

### TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,87
Flash point	°C	DIN ISO 2592	>200
Pour point	°C	DIN ISO 3016	- 28
Viscosity at 40°C	mm <sup>2</sup> /sec	DIN 51562	28,5
Viscosity at 100°C	mm <sup>2</sup> /sec	DIN 51562	5,00

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: [info@rektol.de](mailto:info@rektol.de) · Internet: [www.rektol.de](http://www.rektol.de)