

GEGRÜNDET 1892

Rektol Klassik Korbach



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL UNIVERSAL OIL 20W-50

20W-50 Universal Oil has been specially developed for vehicles in which gearbox and engine have the same oil circuit. Application: for example Mini Cooper, NSU Prinz, Honda 750 Four ...

- Above-average high temperature performance → increased SAE 50 viscosity at least of 20 cSt at 100 °C (please see typical characteristic)
- Lower oil consumption
- Improved wear protection for start and warm up phase
- Stable lubricating film at high oil temperatures

Furthermore Rektol UNIVERSAL OIL 20W-50 is suitable for engines of the older construction machines as well as for circular lubrication and hydrostatic drives. The original oil formulation according to specification API SF/CC GL3 was an inherent part of our product range in our in-house production from 1960s until the 1970s.

SPECIFICATIONS

API-SF/CC (ENGINE)

API GL 3 (TRANSMISSION)

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,89
Flash point	°C	DIN ISO 2592	>230
Pour point	°C	DIN ISO 3016	- 18
Viscosity at 40°C	mm ² /sec	DIN 51562	180,0
Viscosity at 100°C	mm ² /sec	DIN 51562	20,0

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de